

TOMCARR

ANYWHERE AND BACK

TM-2

NO PREVIOUS EXPERIENCE REQUIRED



TM-2

NO PREVIOUS EXPERIENCE REQUIRED



DIMENSIONS:

	TM25i/J*	TM27G/D*
LENGTH:	111"(2820mm)	111"(2820mm)
WIDTH:	65"(1650mm)	70"(1780mm)
HEIGHT:	64"(1625mm)	67"(1686mm)
WHEEL BASE:	81"(2052mm)	81"(2052mm)
GROUND CLEARANCE:	12"(317mm)	15"(378mm)
DRY WEIGHT:	1342lbs. (610Kg) / 1392lbs. (632Kg)*	1551lbs. (705Kg) / 1573lbs. (715Kg)*
ENGINE:	725cc, Gasoline, V twin Cylinder Fuel Injected, Air Cooled / Liquid Cooled*	953cc, Gasoline / 953cc, Turbo Diesel* 3 Cylinder, Liquid Cooled
TRANSMISSION:	Automatic V-Belt CVT. Rear Wheel Drive Final Drive: Oil Bathed Chains / High-Low Gear Box* Forward - Neutral -Reverse, Differential Gear Box Differential Lock*	Automatic V-belt CVT, Heavy Duty, High-Low Gear Box Rear Wheel Drive, Final Drive: Oil Bathed Chains Forward - Neutral - Reverse, Differential Lock
CARGO BOX:	Rails: 54.7" x 31.1"(1389mm x 790mm)	
TOWING LOAD:	990lbs. (450Kg)	1320lbs. (600Kg)
CARGO BOX PAYLOAD:	330lbs. (150Kg)	440lbs. (200Kg)
TIRES:	Front: AT 25 X 8 – 12 Rear: AT 26 X 12 – 12	
SUSPENSION:	Front: Double Wishbone, Heavy Duty Travel: 10.5"(267mm) Rear: Trail Arm, Heavy Duty Travel: 11.5"(292mm) All with adjustable dual coil over springs, gas/hydraulic shocks	Travel: 13.5"(343mm) Travel: 13"(334mm)
STEERING:	Rack and Pinion 1.6 Turn Lock to Lock	
BRAKES:	Hydraulic Power brakes 4 Drums	
FUEL:	6.75 Gallon/26 Liter safety tank (1 or 2 tanks)	
ELECTRIC:	12V 46AH Battery. Alternator + Regulator 25A Power Socket, Halogen Head Lights, Tail Lights, Brake Lights, Horn	12V 46AH Battery. Alternator + Regulator 40A
INSTRUMENTATION:	Speedometer, Wheels Hour Meter, Voltmeter, Fuel Gauge, Low Oil Pressure, Turn Signal, High/Low Beam Temperature Gauge*	Temperature Gage
SEAT:	Adjustable, Bucket Type, Head Rest, 4 Point Safety Harness	

